STORMWATER OPERATION AND MAINTENANCE AGREEMENT AND SECURITY

Project Name:			<u></u>
Town Project Number:_			<u> </u>
Town BMP ID:			
PIN Number:			<u> </u>
Mail after recording to:			
NORTH CAROLINA			
WAKE COUNTY			
This STORMWATER O	OPERATION AND MAI	NTENANCE AGREE	EMENT AND SECURITY
made this day	of	, 20	
by			
	is		
with, to, and for the ben	efit of the Town of Morri	sville, a municipal co	•

Filter Strip, Restored Riparian Buffer and Level Spreader Operation and Maintenance Agreement

I will keep a maintenance record on this BMP. This maintenance record will be kept in a log in a known set location. Any deficient BMP elements noted in the inspection will be corrected, repaired or replaced immediately. These deficiencies can affect the integrity of structures, safety of the public, and the removal efficiency of the BMP.

Important maintenance procedures:

- Immediately after the filter strip is established, any newly planted vegetation will be watered twice weekly if needed until the plants become established (commonly six weeks).
- Once a year, the filter strip will be reseeded to maintain a dense growth of vegetation
- Stable groundcover will be maintained in the drainage area to reduce the sediment load to the vegetation.
- Two to three times a year, grass filter strips will be mowed and the clippings harvested to promote the growth of thick vegetation with optimum pollutant removal efficiency. Turf grass should not be cut shorter than 3 to 5 inches and may be allowed to grow as tall as 12 inches depending on aesthetic requirements (NIPC, 1993). Forested filter strips do not require this type of maintenance.
- Once a year, the soil will be aerated if necessary.
- Once a year, soil pH will be tested and lime will be added if necessary.

After the filter strip is established, it will be inspected quarterly and within 24 hours after every storm event greater than 1.0 inch. Records of operation and maintenance will be kept in a known set location and will be available upon request.

Inspection activities shall be performed as follows. Any problems that are found shall be repaired immediately.

BMP element:	Potential problem:	How I will remediate the problem:
The entire filter strip	Trash/debris is present.	Remove the trash/debris.
system	_	
The flow splitter device (if	The flow splitter device is	Unclog the conveyance and dispose of
applicable)	clogged.	any sediment off-site.
	The flow splitter device is	Make any necessary repairs or replace if
	damaged.	damage is too large for repair.

BMP element:	Potential problem:	How I will remediate the problem:
The swale and the level lip	The swale is clogged with	Remove the sediment and dispose of it
-	sediment.	off-site.
	The level lip is cracked, settled,	Repair or replace lip.
	undercut, eroded or otherwise	
	damaged.	
	There is erosion around the end	Regrade the soil to create a berm that is
	of the level spreader that shows	higher than the level lip, and then plant
	stormwater has bypassed it.	a ground cover and water until it is
		established. Provide lime and a one-
		time fertilizer application.
	Trees or shrubs have begun to	Remove them.
	grow on the swale or just	
	downslope of the level lip.	
The bypass channel	Areas of bare soil and/or erosive	Regrade the soil if necessary to remove
	gullies have formed.	the gully, and then reestablish proper
		erosion control.
	Turf reinforcement is damaged	Study the site to see if a larger bypass
	or ripap is rolling downhill.	channel is needed (enlarge if
		necessary). After this, reestablish the
TF1 (*14 4 * -		erosion control material.
The filter strip	Grass is too short or too long (if	Maintain grass at a height of
	applicable).	approximately three to six inches.
	Areas of bare soil and/or erosive	Regrade the soil if necessary to remove
	gullies have formed.	the gully, and then plant a ground cover and water until it is established.
		Provide lime and a one-time fertilizer
		application.
	Sediment is building up on the	Remove the sediment and restabilize the
	filter strip.	soil with vegetation if necessary.
	inter surp.	Provide lime and a one-time fertilizer
		application.
	Plants are desiccated.	Provide additional irrigation and
		fertilizer as needed.
	Plants are dead, diseased or	Determine the source of the problem:
	dying.	soils, hydrology, disease, etc. Remedy
		the problem and replace plants. Provide
		a one-time fertilizer application.
	Nuisance vegetation is choking	Remove vegetation by hand if possible.
	out desirable species.	If herbicide is used, do not allow it to
	_	get into the receiving water.
The receiving water	Erosion or other signs of damage	Contact the Stormwater Division of the
_	have occurred at the outlet.	Town of Morrisville Engineering
		Department at 919-463-7025.

BMP Operation and Maintenance Security

Performance Security

The Town of Morrisville requires the submittal of a performance security prior to issuance of a permit in order to ensure that the *structural BMP*s are

- 1. installed by the permit holder as required by the approved stormwater management plan, and/or
- 2. maintained by the *owner* as required by the operation and maintenance agreement.

Installation Amount

The amount of an installation performance security shall be the total estimated construction cost of the BMPs approved under the permit, plus 25%.

General Requirements

- 1. This agreement grants to the Town of Morrisville a right of entry to inspect, monitor, maintain, repair, and reconstruct *structural BMPs*.
- 2. The Town of Morrisville is authorized to recover from the property owner and/or association and its members, any and all costs the Town of Morrisville expends to maintain or repair the *structural BMP*s or to correct any operational deficiencies. Failure to pay the Town of Morrisville all of its expended costs, after forty-five days written notice, shall constitute a breach of the agreement. The Town of Morrisville shall thereafter be entitled to bring an action against the property owner and/or association and its members to pay, or foreclose upon the lien hereby authorized by the agreement against the property, or both, in case of a deficiency. Interest, collection costs, and attorney fees shall be added to the recovery.
- 3. This agreement shall not obligate the Town of Morrisville to maintain or repair any *structural BMP*s, and the Town of Morrisville shall not be liable to any person for the condition or operation of *structural BMP*s.
- 4. This agreement shall not in any way diminish, limit, or restrict the right of the Town of Morrisville to enforce any of its ordinances as authorized by law.
- 5. The property owner and/or association and its members indemnifies and holds harmless the Town of Morrisville for any costs and injuries arising from or related to the structural BMP, unless the Town of Morrisville has agreed in writing to assume the maintenance responsibility for the BMP and has accepted dedication of any and all rights necessary to carry out that maintenance.
- 6. The property owner and/or association shall continuously operate and maintain the stormwater control and management facilities.

Uses of Performance Security

1. Forfeiture Provisions

The performance security shall contain forfeiture provisions for failure, after proper notice, to complete work within the time specified, or to initiate or maintain any actions which may be required of the applicant or *owner* in accordance with this ordinance, approvals issued

pursuant to this ordinance, or an operation and maintenance agreement established pursuant to this ordinance.

2. Default

Upon default of the *owner* to construct and, if necessary, reconstruct any *structural BMP* in accordance with the applicable permit, the Stormwater Administrator shall obtain and use all or any portion of the security to make necessary improvements based on an engineering estimate. Such expenditure of funds shall only be made after requesting the *owner* to comply with the permit.

3. Costs in Excess of Performance Security

If the Town of Morrisville takes action upon such failure by the applicant or *owner*, the Town of Morrisville may collect from the applicant or *owner* for the difference should the amount of the reasonable cost of such action exceed the amount of the security held.

4. Refund

After the Town's final approval of record drawings, as-builts and certifications, the installation performance security shall be refunded to the applicant or terminated, in accordance with the Town of Morrisville Unified Development Ordinance (UDO) and Engineering Design and Construction Manual (EDCM).

I acknowledge and agree by my signature below that I am responsible for the performance of the maintenance procedures listed above. I agree to notify the Town of Morrisville of any problems with the system or prior to any changes to the system or responsible party.

Project name:	
BMP drainage area number:	
Print name:	
Date:	
	ld not be a homeowners association unless more than 50% of ent of the subdivision has been named the president.
I,	, a Notary Public for the State of
, County of	do hereby certify that
	personally appeared before me this
	_, and acknowledge the due execution of the
	and/or level spreader maintenance requirements.
Witness my hand and official seal,	
•	
SEAL	l e e e e e e e e e e e e e e e e e e e
My commission expires	

	Town of Morrisville, North Carolina
	Signature: Print Name:
	Title:
Acknowledgment of Town of N	Morrisville:
Wake County, North Carolina	
certify that the following person	on personally appeared before me this day and acknowledged to
me that he or she executed the f	Foregoing document on behalf of the Town of Morrisville in the
capacity indicated with his or he	er signature:
Date:(affix notary seal or stamp here	
	Notary Public
	Printed/Typed Name:
	My Commission Expires: