# STORMWATER OPERATION AND MAINTENANCE AGREEMENT AND SECURITY

Project Name:			_
Town Project Number:	_		_
Town BMP ID:			_
PIN Number:			_
Mail after recording to:	Town of Morrisville Engineering Departmen 100 Town Hall Drive Morrisville, NC 27560		
NORTH CAROLINA			
WAKE COUNTY			
This STORMWATER (	OPERATION AND MA	INTENANCE AGREEM	IENT AND SECURITY
made this day	_ of	, 20	
by		<del> </del>	
	s is		
with, to, and for the ben		risville, a municipal corp Hall Drive, Morrisville, N	

## Sand Filter with Underground Detention Operation and Maintenance Agreement

I will keep a maintenance record on this BMP. This maintenance record will be kept in a log in a known set location. Any deficient BMP elements noted in the inspection will be corrected, repaired or replaced immediately. These deficiencies can affect the integrity of structures, safety of the public, and the removal efficiency of the BMP.

Important maintenance procedures:

- The drainage area will be carefully managed to reduce the sediment load to the sand filter.
- The sedimentation chamber or forebay will be cleaned out whenever sediment depth exceeds six inches.
- Once a year, sand media will be skimmed.
- The sand filter media will be replaced whenever it fails to function properly after maintenance.
- Once a year the underground facility will be thoroughly inspected for structural issues.
- Sediment must be removed from the pipe/vault system when the sediment accumulation depth is inches or greater at any point within the storage pipe/vault.

The sand filter with underground detention will be inspected quarterly and within 24 hours after every storm event greater than 1.0 inches. Records of operation and maintenance will be kept in a known set location and will be available upon request.

Inspection activities shall be performed as follows. Any problems that are found shall be repaired immediately.

BMP element:	Potential problem:	How I will remediate the problem:
Entire BMP	Trash/debris is present.	Remove the trash/debris.
Adjacent pavement (if applicable)	Sediment is present on the pavement surface.	Sweep or vacuum the sediment as soon as possible.
Flow diversion structure	The structure is clogged.	Unclog the conveyance and dispose of any sediment offsite.
	The structure is damaged.	Make any necessary repairs or replace if damage is too large for repair.
The inlet device	The inlet pipe is clogged.	Unclog the pipe. Dispose of the sediment off-site.
	The pipe is cracked or otherwise damaged (if applicable).	Replace the pipe.
	The structure is damaged.	Make any necessary repairs or replace if damage is too large for repair.
Forebay or pretreatment area	Sediment has accumulated to a depth of greater than six inches.	Search for the source of the sediment and remedy the problem if possible. Remove the sediment and stabilize or dispose of it in a location where it will not cause impacts to streams or the BMP.
	Erosion has occurred.	Provide additional erosion protection such as reinforced turf matting or riprap if needed to prevent future erosion problems.
	Weeds are present.	Remove the weeds, preferably by hand. If a herbicide is used, wipe it on the plants rather than spraying.

BMP element:	Potential problem:	How I will remediate the problem:
Filter bed and underdrain collection system	Water is ponding on the surface for more than 24 hours after a storm, and/or the infiltration rate of the sand is less than 2 inches per hour.	Check to see if the collector system is clogged and flush if necessary. If water still ponds, remove the top few inches of filter bed media and replace. If water still ponds, then consult an expert.
The underground vaults/pipes	Sediment accumulation of four inches or more at any point within the storage pipe/vault.  Significant seepage or settlement accompanied by cracking within a small area of	Remove sediment.  Retain assistance of a civil or geotechnical engineer qualified in the design of underground detention
	the vault/pipe system.  Interior wall of pipe/vault shows signs of improper joint alignment (sagging), elongation and displacement of joints, cracks, leaks, surface water, surface wear, loss of protective coating, corrosion and blocking.	systems.  Retain assistance of a civil or geotechnical engineer qualified in the design of underground detention systems.
Outlet device	Clogging has occurred.  The outlet device is damaged The outflow pipe is clogged.	Clean out the outlet device. Dispose of the sediment offsite.  Repair or replace the outlet device.  Provide additional erosion protection such as reinforced turf matting or riprap if needed to prevent future erosion problems.
Receiving water	The outflow pipe is damaged.  Erosion or other signs of damage have occurred at the outlet.	Repair or replace the pipe.  Contact the Stormwater Division of the Town of Morrisville Engineering Department at 919-463-7025.

# **BMP Operation and Maintenance Security**

#### Performance Security

The Town of Morrisville requires the submittal of a performance security prior to issuance of a permit in order to ensure that the *structural BMP*s are

- 1. installed by the permit holder as required by the approved stormwater management plan, and/or
- 2. maintained by the *owner* as required by the operation and maintenance agreement.

#### <u>Installation Amount</u>

The amount of an installation performance security shall be the total estimated construction cost of the BMPs approved under the permit, plus 25%.

#### General Requirements

- 1. This agreement grants to the Town of Morrisville a right of entry to inspect, monitor, maintain, repair, and reconstruct *structural BMP*s.
- 2. The Town of Morrisville is authorized to recover from the property owner and/or association and its members, any and all costs the Town of Morrisville expends to maintain or repair the *structural BMP*s or to correct any operational deficiencies. Failure to pay the Town of Morrisville all of its expended costs, after forty-five days written notice, shall constitute a breach of the agreement. The Town of Morrisville shall thereafter be entitled to bring an action against the property owner and/or association and its members to pay, or foreclose upon the lien hereby authorized by the agreement against the property, or both, in case of a deficiency. Interest, collection costs, and attorney fees shall be added to the recovery.
- 3. This agreement shall not obligate the Town of Morrisville to maintain or repair any *structural BMP*s, and the Town of Morrisville shall not be liable to any person for the condition or operation of *structural BMP*s.
- 4. This agreement shall not in any way diminish, limit, or restrict the right of the Town of Morrisville to enforce any of its ordinances as authorized by law.
- 5. The property owner and/or association and its members indemnifies and holds harmless the Town of Morrisville for any costs and injuries arising from or related to the structural BMP, unless the Town of Morrisville has agreed in writing to assume the maintenance responsibility for the BMP and has accepted dedication of any and all rights necessary to carry out that maintenance.
- 6. The property owner and/or association shall continuously operate and maintain the stormwater control and management facilities.

#### Uses of Performance Security

#### 1. Forfeiture Provisions

The performance security shall contain forfeiture provisions for failure, after proper notice, to complete work within the time specified, or to initiate or maintain any actions which may be required of the applicant or *owner* in accordance with this ordinance, approvals issued

pursuant to this ordinance, or an operation and maintenance agreement established pursuant to this ordinance.

#### 2. Default

Upon default of the *owner* to construct and, if necessary, reconstruct any *structural BMP* in accordance with the applicable permit, the Stormwater Administrator shall obtain and use all or any portion of the security to make necessary improvements based on an engineering estimate. Such expenditure of funds shall only be made after requesting the *owner* to comply with the permit.

### 3. Costs in Excess of Performance Security

If the Town of Morrisville takes action upon such failure by the applicant or *owner*, the Town of Morrisville may collect from the applicant or *owner* for the difference should the amount of the reasonable cost of such action exceed the amount of the security held.

# 4. Refund

After the Town's final approval of record drawings, as-builts and certifications, the installation performance security shall be refunded to the applicant or terminated, in accordance with the Town of Morrisville Unified Development Ordinance (UDO) and Engineering Design and Construction Manual (EDCM).

I acknowledge and agree by my signature below that I am responsible for the performance of the maintenance procedures listed above. I agree to notify the Town of Morrisville of any problems with the system or prior to any changes to the system or responsible party.

Project name:	
Print name:	
Print name:	
Address:	
Phone:	
Signature:	
Date:	
the lots have been sold and a resident of	t be a homeowners association unless more than 50% of f the subdivision has been named the president.
I,	, a Notary Public for the State of
, County of	, do hereby certify that
	personally appeared before me this
day of,, a	and acknowledge the due execution of the
forgoing sand filter maintenance require	ments. Witness my hand and official seal,
SEAL	
My commission expires_	

	Town of Morrisville, North Carolina	
	Signature: Print Name: Title:	
Acknowledgment of Town of M	Iorrisville:	
Wake County, North Carolina		
I certify that the following person personally appeared before me this day and acknowledged to		
me that he or she executed the foregoing document on behalf of the Town of Morrisville in the		
capacity indicated with his or he	er signature:	
Date:(affix notary seal or stamp here)		
	Notary Public	
	Printed/Typed Name:	
	My Commission Expires:	